

10/531130

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
29 April 2004 (29.04.2004)

PCT

(10) International Publication Number
WO 2004/035301 A2

(51) International Patent Classification⁷: **B29D 30/24**

RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR,
TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(21) International Application Number:

PCT/NL2003/000698

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(22) International Filing Date: 15 October 2003 (15.10.2003)

(25) Filing Language:

Dutch

(26) Publication Language:

English

(30) Priority Data:

1021668

16 October 2002 (16.10.2002) NL

(71) Applicant (for all designated States except US): VMI EPE HOLLAND B.V. [NL/NL]; Gelriaweg 16, NL-8161 RK Epe (NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): SLOTS, Tonnie [NL/NL]; Stokvisweg 5, NL-8111 RS Heeten (NL). GROLLEMAN, Henk-Jan [NL/NL]; Jan Mankestraat 3a, NL-6961 CC Eerbeek (NL).

(74) Agents: FERGUSON, Alexander et al.; Octrooibureau Vriesendorp & Gaade, P.O. Box 266, NL-2501 AW The Hague (NL).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT,

Declaration under Rule 4.17:

— as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

Published:

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: TITLE: TYRE DRUM WITH TURN-UP MECHANISM FOR BUILDING AN UNVULCANIZED TYRE

(57) Abstract: Tyre drum including a turn-up mechanism, the tyre drum being provided with a central shaft, two ring segments placed around the shaft and spaced apart for supporting the bead cores and the tyre drum on either side outside of the ring segments being provided with a set of axially extending arms, the arms at a first free end oriented towards the ring segment being provided with a first turn-up means, particularly a turn-up roller, and at an opposite second end being hinged to an axially shiftable arm support, near the first end at least a part of the arms being provided with means for supporting the tyre component, the support means in an initial position forming a circumferential support surface for the tyre components, the tyre drum further being provided with means for shifting the arm supports in order to move the second ends of both sets of arms axially towards each other, the arms being tiltable in radial planes from the initial position to a tilting position in order to thus move the first ends axially and radially while pressing the part of the tyre components situated outside of the ring segments against the expanded part of the tyre components situated within the ring segments, the support means comprising one or more support rollers provided with a support surface for the tyre component, which support roller is rotatably arranged on the arm.

WO 2004/035301 A2